

526A

Swing Arm Tire Changer

526A IT**Features:**


- 1 Strong column with 5mm thickness;
- 2 High quality and wear-resisting alloy demount head and clamping jaw;
- 3 Cabinet with 3mm thickness, to be very strong and solid;
- 4 Aluminium-alloy pedal, to be sturdy and durable;
- 5 Large air cylinder with working output of 2500kg;
- 6 Integrated shovel arm with high tensile strength;
- 7 Pull type pedal assembly with guide rail, to be easy and convenient for maintenance.

Technical data

| | GC-526A | GC-526B | GC-528B |
|---------------------|------------------------------|-----------------|-----------------|
| Model | GC-526A | GC-526B | GC-528B |
| Outer clamp | 12"-24" | 12"-24" | 14"-26" |
| Inner clamp | 14"-26" | 14"-26" | 16"-28" |
| Max. wheel width | 16" | 16" | 16" |
| Max. wheel diameter | 47" | 47" | 51" |
| Air supply | 8-10bar | 8-10bar | 8-10bar |
| Power | 1.1kw | 1.1kw | 1.1kw |
| Power supply | 110/240/380V/1PH/3PH 50/60HZ | | |
| Net Weight | 213kg | 221kg | 250kg |
| Gross weight | 253kg | 261kg | 290kg |
| Packing dimension | 1150×900×1025mm | 1150×900×1025mm | 1150×900×1100mm |

Standard parts**Optional parts**

Motorcycle clamping jaw



8L hand held inflator



20L fixed inflation system